

## 2012 Vortec Response LX Specifications



Length	6.1m or 20 feet
Beam	2.29m or 7'6"
Weight (approx)	1111Kg
Fuel storage capacity	125lt
Max. People	Seven
Towing weight (approx)	1551Kg

All 2012 Vortec models are standard with a carburetted "Indmar 310 Vortec" marine V8 engine including F-N-R transmission.

### STANDARD FEATURES

"Bow Rider" Open Bow design  
 Rockford Fosgate AM/FM MP3/CD Head Unit & 4 RF Speakers  
 SV 23 Diamond Hull  
 100% fibreglass construction utilising FibECS  
 Marine mufflers  
 5" Faria instrumentation with chrome bezel  
 Auto bilge pump  
 Bilge blower  
 Horn  
 Accessory switches with circuit breaker protection  
 Tilt helm rack and pinion steering with adjustable rudder  
 Stainless steel steering components  
 Sports steering wheel  
 Fully carpeted with premium 32oz poly/heat set marine carpet  
 38oz duraguard G&T vinyl French stitched interior  
 Triple density "Tri-Ply" foam cushioning  
 Stainless grab handles throughout interior  
 Adjustable drivers seat with seat slides & lumbar support  
 Tempered safety glass windscreen with bow access door  
 Lockable glove box  
 1 1/8th shaft with cutless shaft bearings  
 Dripless water cooled shaft seal  
 13 X 12 3 blade CNC cut and tuned nibral prop  
 Solid core 2 1/2" aluminium ski pole with patented swivel head  
 Illuminated storage including side pocket storage  
 Lockable rear storage trunk with light  
 Built in esky  
 Fibreglass Swim Platform  
 Stainless rear ski tow/handle  
 Removable rear seat  
 "In laminate" acoustic insulation (Malibu sound suppression layer)  
 Oversized cup holders  
 Flush kit - Stainless steel - external access  
 Deep cycle marine battery with isolator switch

### STANDARD TRAILER FEATURES

Fully galvanised custom fitted tandem trailer  
 Inertia operated disc brakes including park brake  
 "Spinner" guide poles  
 Rear trolley wheels  
 Jockey wheel and winch  
 15" Alloy wheels