

2012 Vortec Response Specifications



Length	6.1m or 20 feet
Beam	2.29m or 7'6"
Weight (approx)	1111Kg
Fuel storage capacity	125lt
Max. People	Six
Towing weight (approx)	1551Kg

All 2012 Vortec models are standard with a carburetted "Indmar 310 Vortec" marine V8 engine including F-N-R transmission.

STANDARD FEATURES

Rockford Fosgate AM/FM MP3/CD Head Unit & 4 RF Speakers
SV 23 Diamond Hull
100% fibreglass construction utilising FibECS
Marine mufflers
5" Faria instrumentation with chrome bezel
Auto bilge pump
Bilge blower
Horn
Accessory switches with circuit breaker protection
Tilt helm rack and pinion steering with adjustable rudder
Stainless steel steering components
Sports steering wheel
Fully carpeted with premium 32oz poly/heat set marine carpet
38oz duraguard G&T vinyl French stitched interior
Triple density "Tri-Ply" foam cushioning
Stainless grab handles throughout interior
Adjustable drivers seat with seat slides & lumbar support
Tempered safety glass windscreen with bow access door
Lockable glove box
1 1/8th shaft with cutless shaft bearings
Dripless water cooled shaft seal
13 X 12 3 blade CNC cut and tuned nibral prop
Solid core 2 1/2" aluminium ski pole with patented swivel head
Illuminated storage including side pocket storage
Lockable rear storage trunk with light
Built in esky
Fibreglass Swim Platform
Stainless rear ski tow/handle
Removable rear seat
"In laminate" acoustic insulation (Malibu sound suppression layer)
Oversized cup holders
Flush kit - Stainless steel - external access
Deep cycle marine battery with isolator switch

STANDARD TRAILER FEATURES

Fully galvanised custom fitted tandem trailer
Inertia operated disc brakes including park brake
"Spinner" guide poles
Rear trolley wheels
Jockey wheel and winch
15" Alloy wheels